



Espacenet

Bibliographic data: JP 2003510853 (T)

SURFACE STRUCTURED LIGHT-EMITTING DIODE WITH IMPROVED CURRENT COUPLING

Publication date: 2003-03-18

Inventor(s):

Applicant(s):

Classification:

- **international:** H01L33/02; H01L33/42; H01L33/14; H01L33/22; (IPC1-7): H01L33/00
- **European:** H01L33/02C; H01L33/42

Application number: JP20010527369T 20000921

Priority number(s): DE19991047030 19990930; WO2000DE03291 20000921


Also published as:

- WO 0124280 (A1)
- US 7135709 (B1)
- TW 513816 (B)
- EP 1222696 (A1)
- DE 19947030 (A1)
- more

Abstract not available for JP 2003510853 (T)

Abstract of corresponding document:
WO 0124280 (A1)

The light output from a light emitting diode (100), comprising a light generating layer (20) and a relatively thick, transparent current dispersing layer (30), is improved by a vertical structuring of the surfaces of the current dispersing layer (30) and, by means of a second electrical contact layer (50) with a distributed lateral structure, an essentially homogeneous coupling of electrical current in the current dispersing layer (30) can be obtained.



Last updated:
26.04.2011 Worldwide
Database 5.7.22; 92p